

LIEBHERR

Contents

001		
1 1.1 1.2 1.3 1.4 1.5 1.6 1.7	Appliance at a glance Scope of delivery Overview of the appliance and features SmartDevice Appliance range of use Conformity SVHC substances according to REACH regulation. EPREL database.	3 3 3 3 4 4 4 4 4
2	General safety instructions	4
3 3.1 3.2 3.3	Functionality of the Touch display Navigation and symbol explanation Menus Sleep mode	6 6 7
4 4.1 4.2	Putting into operation Switching on appliance (first use) Starting the EasyTwist-Ice for the first time*	7 7 7
5 5.1 5.2 5.3 5.4 5.5	Storage Information regarding storage Fridge compartment EasyFresh Freezer compartment Storage times	7 7 8 8 8 8
6	Saving energy	9
7 7.1 7.1.1 7.1.2 7.2 7.2.1	Controls Controls and displays Status display Display symbols Appliance functions Notes on the appliance functions Switching the appliance off and on	9 9 9 9
-18 °c	WiFi	
• 5 ·c	Temperature	. 11
°C⁄~F	Temperature unit	
D1	SuperCool	
$\frac{\wedge}{(\mathcal{A})}$	PowerCool	. 12
**	SuperFrost	.13
*\()	Start defrosting cycle	
Ŵ	PartyMode	
	HolidayMode	
¥	E-Saver	
	CleaningMode	.16

-) 0 /-	Display brightness	16
	Door alarm	16
×îm	Input lock	17
Service No: Model Index: Secure:	Device information	17
H SW: 10000000 HB SW: XXXXIIIDDX Software	Software	17
۲ <u>۲</u> ۲	Reminder	17
\bigcirc	Demo mode	18
\bigcirc	Resetting to factory settings	19
7.3	Messages	19
7.3.1	Overview of warnings	19
7.3.2	Ending warnings	
7.3.3	Overview of reminders	.20
7.3.4	Ending reminders	. 20
0	Features	20
8		
8.1	Door rack	20
		01
8.2	Shelves	21
8.3	Dividing shelf*	21
8.3 8.4	Dividing shelf* VarioSafe *	21 22
8.3 8.4 8.5	Dividing shelf* VarioSafe * Drawers	21 22 24
8.3 8.4 8.5 8.6	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover	21 22 24 24
8.3 8.4 8.5 8.6 8.7	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels	21 22 24 24 25
8.3 8.4 8.5 8.6 8.7 8.8	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves	21 22 24 24 25 25
8.3 8.4 8.5 8.6 8.7 8.8 8.9	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice*	21 22 24 24 25 25 25
8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace	21 22 24 24 25 25 25 25 26
8.3 8.4 8.5 8.6 8.7 8.8 8.9	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice*	21 22 24 24 25 25 25
8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance	21 22 24 24 25 25 25 25 26
8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10 8.11	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance FreshAir carbon filter	21 22 24 25 25 25 25 26 26 26 27
8.3 8.4 8.5 8.6 8.7 8.8 8.7 8.8 8.9 8.10 8.11 9 9.1 9.2	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance FreshAir carbon filter Disassembling / assembling pull-out systems	21 22 24 25 25 25 25 26 26 26 27 27 27
8.3 8.4 8.5 8.6 8.7 8.8 8.7 8.8 8.9 8.10 8.11 9 9.1 9.2 9.3	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance FreshAir carbon filter Disassembling / assembling pull-out systems Defrosting the appliance	21 22 24 25 25 25 26 26 26 27 27 27 27
8.3 8.4 8.5 8.6 8.7 8.8 8.7 8.8 8.9 8.10 8.11 9 9.1 9.2	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance FreshAir carbon filter Disassembling / assembling pull-out systems	21 22 24 25 25 25 26 26 26 26 27 27
8.3 8.4 8.5 8.6 8.7 8.8 8.7 8.8 8.9 8.10 8.11 9 9.1 9.2 9.3	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance FreshAir carbon filter Disassembling / assembling pull-out systems Defrosting the appliance	21 22 24 25 25 25 26 26 26 27 27 27 27
8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10 8.11 9.1 9.1 9.2 9.3 9.4 10	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance FreshAir carbon filter Disassembling / assembling pull-out systems Defrosting the appliance Cleaning the appliance Customer help	21 22 24 25 25 25 26 26 26 26 27 27 27 27 27 30
8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10 8.11 9.1 9.2 9.3 9.4	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance FreshAir carbon filter Disassembling / assembling pull-out systems Defrosting the appliance Cleaning the appliance Customer help Technical specifications	21 22 24 25 25 25 26 26 26 26 27 27 27 27 27 27 27
8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10 8.11 9.1 9.1 9.2 9.3 9.4 10 10.1	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance FreshAir carbon filter Disassembling / assembling pull-out systems Defrosting the appliance Cleaning the appliance Customer help Technical specifications Operating noises	21 22 24 25 25 25 25 25 26 26 26 27 27 27 27 27 27 30 30
8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10 8.11 9.1 9.1 9.2 9.3 9.4 10 10.1 10.2	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance. FreshAir carbon filter. Disassembling / assembling pull-out systems Defrosting the appliance. Cleaning the appliance. Cleaning the appliance. Cleaning the appliance. Technical specifications. Operating noises Technical fault.	21 22 24 25 25 25 26 26 26 27 27 27 27 27 27 30 30 30 31
8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10 8.11 9.1 9.1 9.2 9.3 9.4 10 10.1 10.2 10.3	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance FreshAir carbon filter Disassembling / assembling pull-out systems Defrosting the appliance Cleaning the appliance Customer help Technical specifications Operating noises	21 22 24 25 25 25 25 25 25 25 25 26 26 27 27 27 27 27 27 30 30 30
8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10 8.11 9.1 9.2 9.3 9.4 10 10.1 10.2 10.3 10.4	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance FreshAir carbon filter Disassembling / assembling pull-out systems Defrosting the appliance Cleaning the appliance Cleaning the appliance Cleaning the appliance Technical specifications Operating noises Technical fault Customer Service	21 22 24 25 25 25 26 26 26 27 27 27 27 27 27 30 30 30 31 32
8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10 8.11 9.1 9.2 9.3 9.4 10 10.1 10.2 10.3 10.4 10.5 11	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance. FreshAir carbon filter. Disassembling / assembling pull-out systems Defrosting the appliance. Cleaning the appliance Cleaning the appliance Customer help Technical specifications. Operating noises Technical fault Customer Service Model plate	21 22 24 25 25 25 26 26 26 26 27 27 27 27 30 30 30 31 32 32 32 32
8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10 8.11 9.1 9.1 9.2 9.3 9.4 10 10.1 10.2 10.3 10.4 10.5 11 12	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance FreshAir carbon filter Disassembling / assembling pull-out systems Defrosting the appliance Cleaning the appliance Cleaning the appliance Cleaning the appliance Customer help Technical specifications Operating noises Technical fault Customer Service Model plate Shutting down	21 22 24 24 25 25 25 26 26 26 27 27 27 27 27 27 30 30 31 32 32 32 32 32 32
8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10 8.11 9.1 9.1 9.2 9.3 9.4 10 10.1 10.2 10.3 10.4 10.5 11 12 12.1	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance. FreshAir carbon filter Disassembling / assembling pull-out systems Defrosting the appliance Cleaning the appliance Cleaning the appliance Cleaning the appliance Customer help Technical specifications Operating noises Technical fault Customer Service Model plate Shutting down Preparing appliance for disposal	21 22 24 25 25 25 26 26 26 26 27 27 27 27 30 30 30 31 32 32 32 32
8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10 8.11 9.1 9.1 9.2 9.3 9.4 10 10.1 10.2 10.3 10.4 10.5 11 12	Dividing shelf* VarioSafe * Drawers EasyFresh-Safe cover Adjusting the moisture levels Glass shelves EasyTwist-Ice* VarioSpace Bottle holder Maintenance FreshAir carbon filter Disassembling / assembling pull-out systems Defrosting the appliance Cleaning the appliance Cleaning the appliance Cleaning the appliance Customer help Technical specifications Operating noises Technical fault Customer Service Model plate Shutting down	21 22 24 24 25 25 25 26 26 26 27 27 27 27 27 27 30 30 31 32 32 32 32 32 32

The manufacturer is continually working on the further development of all types and models. Please be aware that we reserve the right to make changes to the shape, equipment and technology.

Symbol	Explanation
	Read instructions Please read the information in these instruc- tions carefully to understand all of the benefits of your new appliance.

Symbol	Explanation
Ċ	Additional information on the Internet The digital manual with additional informa- tion and in other languages can be found via the QR code on the front of the manual or by entering the service number at home.liebherr.com/fridge-manuals. The service number can be found on the serial tag:
	<i>Fig.</i> Example illustration Check appliance Check all parts for transport damage. If you have any complaints, please contact your agent or customer service.
*	Differences These instructions apply to a range of models, so differences are possible. Sections that apply to certain models only are marked with an asterisk (*).
\land	Instructions and results Instructions are marked with a ▶. Results are marked with a ▷.
	Videos Videos about the appliances are available on the YouTube channels of Liebherr-Hausgeräte.

These operating instructions apply to:

50 / 52 / 57 / 76 / 77
52Z03 / 57Z03
52Vc03 / 52Vd03 / 57Vc03 / 57Vd03 / 57Va03
1863 / 2063

Note

If your appliance has an N in its appliance designation, it is a NoFrost appliance.

1 Appliance at a glance

1.1 Scope of delivery

Check all parts for transport damage. Contact your dealer or customer service in the event of complaints. (see 10.4 Customer Service)

Your new appliance comes with the following parts:

- -Standalone appliance
- Features (depending on the model) _
- Installation materials (depending on the model) _
- "Quick Start Guide"
- "Installation Guide"
- Service Brochure

1.2 Overview of the appliance and features



Fig. 1 Example illustration

- **Temperature range**
- (A) Fridge compartment
 - (B) EasyFresh
 - (1) Controls
 - (9) EasyFresh safe (2) Fan with FreshAiracti-(10) Freezer compartment

Features

(C) Freezer compartment

(D) Coldest zone

(12) Serial tag

(13) Bottle holder

(14) Bottle rack

- vated charcoal filter (11) VarioSpace
- (3) Separable storage
- shelf*
- (4) Storage shelve
- (5) VarioSafe* (6) Bottle shelf*
- (7) EasyFresh safe cover (15) Can rack (8) Outlet (16) EasyTwist-Ice*

Note

Shelves, drawers and baskets are arranged for optimum energy efficiency when the appliance is delivered. Changing how the shelves, for example, are inserted in the fridge compartment does not have any impact on energy consumption.

1.3 SmartDevice

SmartDevice is the networking solution for your fridgefreezer.

If your appliance SmartDevice-enabled or compatible, you can quickly and easily connect your appliance to your WiFi. With the SmartDevice app, you can operate your appliance from a mobile device. Additional functions and setting options are available in the SmartDevice SmartDevice app.

General safety instructions

SmartDeviceance:

Your appliance is compatible for use compatible appli- with the SmartDeviceBox. You must first purchase and install the Smart-DeviceBox. In order to connect your appliance to the WiFi, you need to download the SmartDevice app.



information smartdevice.liebherr.com More about SmartDevice:

Purchasing SmartDeviceBox in the Liebherr-Hausgeräte store:

the home.liebherr.com/shop/de/deu/ smartdevicebox.html

Downloading the SmartDevice app:



After installing and configuring the SmartDevice, you can connect your appliance to the WiFi using the SmartDevice app and the WiFi appliance function (see WiFi).

Note

The SmartDevice function is not available in the following countries: Russia, Belarus, Kazakhstan.

You cannot use the SmartDeviceBox.

1.4 Appliance range of use

Intended use

The appliance is only suitable for cooling food products in a domestic or household-like environment. This includes, for example, use:

- in staff kitchens, bed and breakfast establishments.
- by guests in country houses, hotels, motels and other accommodation,
- for catering and similar services in the wholesale trade.

The appliance is not suitable as a built-in unit.

All other types of use are not permitted.

Foreseeable misuse

The following applications are expressly forbidden:

- Storing and refrigerating medicines, blood plasma, laboratory preparations or similar substances and products based on the Medical Device Directive 2007/47/EC
- Use in areas at risk of explosions

Misusing the appliance may lead to damage to the goods stored or they may spoil.

Climate classifications

Depending on the climate classification the appliance is designed to operate in restricted ambient temperatures. The climate classification applying to your appliance is printed on the rating plate.

Note

Keep to the specified ambient temperatures in order to guarantee that the appliance works properly.

Climate clas- sification	for ambient temperatures of
SN	10 °C to 32 °C
N	16 °C to 32 °C
ST	16 °C to 38 °C
Т	16 °C to 43 °C
SN-ST	10 °C to 38 °C
SN-T	10 °C to 43 °C

1.5 Conformity

The refrigerant circuit has been tested for leaks. The appliance complies with the applicable safety regulations and with the corresponding directives.

The full text of the EU Declaration of Conformity is available on the following website: www.Liebherr.com

1.6 SVHC substances according to **REACH** regulation

You can check whether your appliance contains SVHC substances according to REACH regulation at the following link: home.liebherr.com/de/deu/de/liebherr-erleben/nachhaltigkeit/umwelt/scip/scip.html

1.7 EPREL database

Details about energy labelling and ecodesign requirements will be available on the European product database (EPREL) from 1st March 2021. You can access the product database at the following link: https://eprel.ec.europa.eu/ You will be asked to enter the model ID. You can find the model ID on the nameplate.

2 General safety instructions

Please keep these operating instructions in a safe place so you can refer back to them at any time.

If you pass the appliance on, please hand these operating instructions to the next user.

Read these operating instructions carefully before use to ensure safe and correct use of the appliance. Follow the instructions, safety instructions and warning messages included at all times. They are important for ensuring you can operate and install the appliance safely and without any problems.

Danger for the user:

 This device can be used by children and people with impaired physical, sensory or mental abilities or with a lack of experience and knowledge provided that they are supervised or have received instruction in the safe use of this device, and about the resulting hazards.

Children must not play with this appliance. Cleaning and user maintenance work must not be carried out by children without adult supervision. Children aged between 3 and 8 are allowed to load and unload the appliance. Children below the age of 3 must be kept away from the appliance unless they are under continuous adult supervision.

- The socket must be easily accessible so that the appliance can be disconnected quickly from the electricity in an emergency. It must not be located in the area behind the appliance.
- When disconnecting the appliance from the supply, always take hold of the plug. Do not pull the cable.
- In the event of a fault pull out the mains plug or deactivate the fuse.
- Do not damage the mains power cable. Do not operate the appliance with a defective mains power cable.
- Only customer service or other specially trained staff may repair or perform other operations on the appliance.
- Only assemble, connect and dispose of the appliance according to the instructions.

Fire hazard:

- The coolant used (information on the model plate) is ecofriendly but also flammable. Any leaking coolant may ignite.
 - Do not damage the refrigerant circuit pipes.
 - Do not handle ignition sources inside the appliance.
 - Do not use electrical appliances inside the appliance (e.g. steam cleaners, heaters, ice cream makers, etc.).
 - If the refrigerant leaks: remove any naked flames or ignition sources from the vicinity of the leakage point. Properly air the room. Inform customer services.
- Do not store explosives or sprays using combustible propellants such as butane, propane, pentane, etc. in the appliance. To identify these spray cans, look for the list of contents printed on the can, or a flame symbol. Gases possibly escaping may ignite due to electrical components.

- Keep burning candles, lamps and other items with naked flames away from the appliance so that they do not set the appliance on fire.
- Please be sure to store alcoholic drinks or other packaging containing alcohol in tightly closed containers. Any alcohol that leaks out may be ignited by electrical components.

Danger of tipping and falling:

- Do not misuse the plinth, drawers, doors etc. as a step or for support. This applies particularly to children.

Danger of food poisoning:

- Do not consume food which has been stored too long.

Danger of frostbite, numbness and pain:

 Avoid prolonged skin contact with cold surfaces or refrigerated/frozen goods or take protective measures, e.g wear gloves.

Danger of injury and damage:

- Hot steam can lead to injury. Do not use electrical heating or steam cleaning equipment, open flames or defrosting sprays to defrost.
- Do not use sharp implements to remove the ice.

Risk of crushing:

- Do not hold the hinge when opening and closing the door. Fingers may get caught.

Symbols on the appliance:



This symbol may be located on the compressor. It relates to the oil in the compressor and makes reference to the risk that: Swallowing or inhaling can be fatal. This advice is only relevant to recycling. There is no danger in normal operation.



This symbol is located on the compressor and indicates the danger of flammable materials. Do not remove the sticker.



This or a similar sticker may be located on the rear of the appliance. This sticker indicates that there are vacuum insulation panels (VIP) or perlite panels in the door and/or housing. This advice is only relevant to recycling. Do not remove the sticker.

Please note the warning messages and other specific advice in the other chapters:



Functionality of the Touch display

WARNING	indicates a hazardous situation which may lead to death or serious injuries if it is not avoided.
CAUTION	indicates a hazardous situation which may lead to minor or moderate injuries if it is not avoided.
NOTICE	indicates a hazardous situation which may lead to damage to property if it is not avoided.
Note	indicates useful instructions and tips.

3 Functionality of the Touch display

You operate your appliance using the Touch display. You select appliance functions in the Touch display (hereafter referred to as display) by tapping them. If you do not perform any action on the display for 10 seconds, the display either jumps back to the higher-level menu or directly to the status display.

3.1 Navigation and symbol explanation

In the illustrations, different symbols are used to navigate the display. The following table describes these symbols.

Symbol	Description
	Press the Next navigation arrow: Navigates to the next option in the menu.
	Press the Back navigation arrow: Jumps back one option in the menu.
	Press the navigation arrow several times in succession: Navigates in the menu to the desired function.
	Press the Confirm symbol: Activates/deactivates function. Opens submenu.
Back	Press the Confirm symbol together with the back icon: Jumps back one menu level.
♦ ©	Arrow with clock: It takes more than 10 seconds for the following message to appear in the display.
	Arrow with a time indication: It takes the specified amount of time until the following message appears in the display.

Symbol		Description
		"Open Settings menu" symbol: Navigates to the Settings menu and opens the settings menu. If necessary: Navigate to the desired function in the Settings menu. (see 3.2.1 Opening the Settings menu)
		"Open Advanced menu" symbol: Navigates to the Advanced menu and opens the advanced menu. If necessary: Navigate to the desired function in the Advanced menu. (see 3.2.2 Opening the Advanced menu)
No action 10 seconds	for	If you do not perform any action on the display for 10 seconds, the display either jumps back to the higher-level menu or directly to the status display.
Opening door closing it again	and	If you open the door and immedi- ately close it again, the display jumps directly back to the status display.

Note: Illustrations of the display are shown in the English version.

3.2 Menus

The appliance functions can be found in various menus.

Menu	Description
Main menu	When you switch the appliance on, you are automatically in the main menu.
	From here you can navigate to the most important appliance functions, to the Settings menu and to the Advanced menu.
Settings Settings	The Settings menu contains additional appliance functions for setting up your appliance. (see 3.2.1 Opening the Settings menu)
menu	
Advanced menu	The advanced menu contains special appli- ance functions for setting up your appli- ance. Access to the Advanced menu is protected by the numerical code 151 . (see 3.2.2 Opening the Advanced menu)

3.2.1 Opening the Settings menu



Fig. 2 Example illustration

- ► Carry out action steps according to the illustration.
- Settings menu is open.
 If necessary: Navigate to the desired function.

3.2.2 Opening the Advanced menu



Fig. 3



Fig. 4 Example illustration, access with numerical code 151
Carry out action steps according to the illustration.

- ▷ The expanded menu is open.
- ▶ If necessary: Navigate to the desired function.

3.3 Sleep mode

If you do not touch the display for 1 minute, the display switches to sleep mode. In sleep mode, the display brightness is dimmed.

3.3.1 Ending sleep mode

- Press any navigation key.
- \triangleright Sleep mode is ended.

4 Putting into operation

4.1 Switching on appliance (first use)

Make sure that the following requirements are fulfilled:

- □ The appliance has been installed and connected in accordance with the installation instructions.
- □ All adhesive strips, adhesive and protective films and transport locks are removed from inside and on the appliance.
- □ All marketing leaflets are removed from the drawers.
- You are familiar with the functionality of the Touch display. (see 3 Functionality of the Touch display)

Switch on the appliance using the Touch display:

- If the display is in sleep mode: Briefly touch the display.
- Carry out action steps according to the illustration.



Fig. 5 Example illustration

- \triangleright The status display appears.
- \triangleright The appliance cools to the temperature set at the factory.
- The appliance starts in demo mode (status display with DEMO appears): If the appliance starts in demo mode, you can deactivate demo mode within the next 5 minutes. (see Demo mode)

More information:

- Start the EasyTwist-Ice for the first time. (see 4.2 Starting the EasyTwist-Ice for the first time*) *
- Start the SmartDevice for the first time. (see 1.3 Smart-Device) and (see WiFi)

Note

The manufacturer recommends:

- Stock with food: Wait for around 6 hours until the set temperature is reached.
- Store frozen foods at -18 °C or colder.
- Observe the notes on storing food. (see 5.1 Information regarding storage)

Note

Accessories can be purchased from the Liebherr-Hausgeräte store at home.liebherr.com/shop/de/deu/zubehor.html.

4.2 Starting the EasyTwist-Ice for the first time*

If your appliance is equipped with EasyTwist-Ice, you must clean the EasyTwist-Ice **before using it for the first time**. Make sure that the following requirements are fulfilled:

□ The appliance is properly connected.

- Clean the EasyTwist-Ice. (see 9.4.6 Cleaning the Easy-Twist-Ice*)
- Fill the water tank. (see Filling the water tank)

5 Storage

5.1 Information regarding storage



Risk of fire

Do not use any electrical appliances in the food area of the appliance unless recommended by the manufacturer.

Note

The energy consumption increases and the cooling power goes down if ventilation is not sufficient.

Always keep air slots clear.

Observe the following specifications for storage:

- In the freezer compartment: Package food properly.
- Package or cover foods that readily take on or give off odours or taste in closed containers.
- Package raw meat or fish in clean, closed containers. This will prevent meat or fish from touching or dripping onto other food.
- Keep liquids in closed containers.
- Leave space between goods to ensure good air circulation.
- Store food according to the instructions on the packaging.
- Always observe the best-before date indicated on the packaging.

Note

Failure to follow these guidelines can lead to foodstuffs spoiling.

5.2 Fridge compartment

The air circulation in the appliance creates different temperature zones. You will find the different temperature zones in the appliance and equipment overview. (see 1.2 Overview of the appliance and features)

5.2.1 Arranging your food properly

- Upper area and door: Store butter, cheese, tinned food and tubes.
- Coldest temperature zone: Store perishable foods such as pre-cooked meals, meat and lunch meats.
- Bottom shelf: Store raw meat or fish.

5.3 EasyFresh 🖒 🖉 🕲

EasyFresh is great for non-packaged foods, such as fruit and vegetables.

The humidity in the compartment depends on the moisture content of the chilled goods placed in it, and also depends on how often the compartment is opened. You can regulate the humidity level. (see 8.7 Adjusting the moisture levels)

5.3.1 Arranging your food properly

- Store unpackaged fruit and vegetables. If the humidity is too high:
- Regulate the humidity. (see 8.7 Adjusting the moisture levels)

5.4 Freezer compartment

Here, a dry, frosty storage climate is created at -18 °C. The frosty storage climate is suitable for storing frozen food for several months, for making ice cubes or freezing fresh food.

5.4.1 Freezing food

Freezing quantity

The maximum amount of fresh food that you can freeze within 24 hours is specified on the type plate (see 10.5 Model plate) under "Freezing capacity ... kg/24h".

To ensure that food quickly freezes through, adhere to the following quantities per package:

- Fruit and vegetables up to 1 kg
- Meat up to 2.5 kg

Freezing food using SuperFrost

Depending on the quantity to be frozen, you can activate SuperFrost before freezing in order to achieve lower freezing temperatures. (see SuperFrost)

Activate SuperFrost if the amount of food you have to freeze is more than approx. 2 kg.

The time at which you activate SuperFrost depends on the amount of food you have to freeze:

Freezing quan- tity	Time at which you should activate SuperFrost
	Activate SuperFrost about 6 hours before freezing. You can place the food in the freezer as soon as the appliance automatically
	deactivates SuperFrost.

Freezing quan-	Time at which you should activate
tity	SuperFrost
Maximum amount of food to freeze	Activate SuperFrost about 24 hours before freezing. You can place the food in the freezer as soon as the appliance automatically deactivates SuperFrost.

Arranging your food properly



Risk of injury from broken glass!

Bottles and cans with beverages can burst during freezing. This applies in particular to carbonated beverages.

Only freeze bottles and cans with beverages if you have activated the BottleTimer function in the SmartDevice app.

Freezing quan- tity	Arranging your food properly
Small amount of food to freeze	Place packaged food in the top drawer. If possible, place groceries at the back of the drawer near the rear wall.
Maximum amount of food to freeze	Distribute packaged groceries throughout all drawers, but only place frozen food in the bottom drawer.
	If possible, place groceries at the back of the drawer near the rear wall.

5.4.2 Defrosting food



Risk of food poisoning!

- ▶ Do not re-freeze thawed food.
- ▶ Use defrosted foodstuff as soon as possible.

You can defrost food in several ways:

- In the fridge compartment
- In the microwave
- In the oven/fan-assisted oven
- At room temperature
- ▶ Take out only as much food as necessary.

5.5 Storage times

Refer to the specified storage times as a guide.

In the case of foods with a minimum shelf life, the date indicated on the packaging still applies.

5.5.1 Fridge section

Always follow the best-before date stated on the packaging.

5.5.2 Freezer compartment

Recommended storage period for various types of food			
Ice cream	at -18 °C	2 to 6 months	
Sausages, ham	at -18 °C	2 to 3 months	
Bread, baked goods	at -18 °C	2 to 6 months	
Game, pork	at -18 °C	6 to 9 months	
Fatty fish	at -18 °C	2 to 6 months	

Recommended storage period for various types of food			
Lean fish	at -18 °C	6 to 8 months	
Cheese	at -18 °C	2 to 6 months	
Poultry, beef	at -18 °C	6 to 12 months	
Vegetables, fruit	at -18 °C	6 to 12 months	

6 Saving energy

- Pay attention to good ventilation. Do not cover ventilation holes or grids.
- Always keep the fan air slits clear.
- Do not place the appliance in direct sunlight or near radiators or similar sources of heat.
- If the appliance is placed directly next to an oven, the energy consumption may increase slightly. This is dependent on the service life and usage intensity of the oven
- Energy consumption depends on the installation conditions, e.g. the ambient temperature (see 1.4 Appliance range of use) . A warmer ambient temperature can increase the energy consumption.
- Open the appliance for as short a time as possible.
- The lower the temperature is set the higher the energy consumption.
- Sort your food: home.liebherr.com/food.
- Keep all food properly packed and covered. This prevents frost from forming.
- Only take food out for as long as necessary so that it doesn't warm up too much.
- Inserting warm food: allow to cool down to room temperature first.
- Thaw frozen food in the refrigerator.
- For longer periods of absence, use HolidayMode (see HolidayMode).

Dust deposits increase energy consumption:

For refrigerators with heat exchangers dust the metal grid on the back of the appliance once a year.



Controls 7

7.1 Controls and displays

7.1.1 Status display



Fig. 6

(1) Temperature display of the fridge section

(2) Freezer compartment temperature display

The Status display shows the set temperature and is the home display. From there, you can navigate to the options and settings.

7.1.2 Display symbols

Display symbols provide information on the current appliance status:



Symbol





Standby

Appliance status

The appliance or temperature zone is switched off.

Flashing number

Appliance is working. Temperature flashes until the set value is reached.



Flashing symbol Appliance is working. Setting is made.

Bar grows steadily

Function is activated.

7.2 Appliance functions

7.2.1 Notes on the appliance functions

The appliance functions are set at the factory so that your appliance is fully functional.

Before you alter, activate or deactivate the device functions, make sure that the following requirements are met:

- □ You have read and understood the descriptions of how the display works. (see 3 Functionality of the Touch display)
- You have familiarised yourself with the operating and display elements of your appliance.



Switching the appliance off and on

Use this function to switch the entire appliance off and on.

Switching off the appliance

When you switch the appliance off, then the previously saved settings are saved.

Make sure that the following requirements are fulfilled:

Handling instructions (see 11 Shutting down) are carried out.



Fig. 7



Fig. 8

- Carry out action steps according to the illustration.
- \triangleright Appliance is switched off.
- \triangleright The standby symbol appears in the display.
- \triangleright Display turns black.

Switching on the appliance

If the display is in sleep mode: Press any navigation key.

Controls



Fig. 9 Example illustration

- Carry out action steps according to the illustration. When the appliance starts in demo mode:
- Deactivating demo mode. (see Deactivating demo mode)
 The appliance is switched on.
- Previous settings are restored.
- \triangleright The appliance cools to the target temperature set.

[⊕] ⁻¹⁸[∞] Switching temperature zone off and on

You can switch temperature zones of the appliance off independently.

Application:

- Cleaning
- Defrosting

Switching the fridge compartment off

Make sure that the following requirements are fulfilled: □ Refrigerator compartment has been emptied.



Fig. 10 Example illustration

- Carry out action steps according to the illustration.
- > Refrigerator compartment is switched off.

Switching the fridge compartment on



- Fig. 11 Example illustration
- Carry out action steps according to the illustration.
- > Refrigerator compartment is switched on.
- \triangleright The appliance cools to the last set temperature.



Use this function to connect your appliance to WiFi. You can then operate it via the SmartDevice app on a mobile device. You can also use this function to disconnect or reset the WiFi connection.

To connect your device to WiFi, you need the SmartDeviceBox.

More information on the SmartDevice: (see 1.3 SmartDevice)

Note

The SmartDevice function is not available in the following countries: Russia, Belarus, Kazakhstan. You cannot use the SmartDeviceBox.

Establishing the WiFi connection for the first time

Make sure that the following requirements are fulfilled:

- □ You have purchased and inserted a SmartDeviceBox. (see 1.3 SmartDevice)
- You have installed the SmartDevice app (see apps.home.liebherr.com).
- Registration in the SmartDevice app is completed.



Fig. 12



Fig. 13

- Carry out action steps according to the illustration.
- \triangleright Connection is established.

Disconnecting from the WiFi



Fig. 14



- Carry out action steps according to the illustration.
- \triangleright There is no connection.

Resetting the WiFi connection



Fig. 16



Fig. 17

- Carry out action steps according to the illustration.
 WiFi connection and other WiFi settings are reset to
- factory settings.

Showing information about the WiFi connection





Fig. 19

• Carry out action steps according to the illustration.

5 ° Temperature

Use this function to set the temperature.

The temperature depends on the following factors:

- Frequency of door opening
- Duration of door opening
- Room temperature of the installation site
- Type, temperature and quantity of food

Temperature zone	Factory-set temperature	Recommended setting
5 ° Fridge section	5 °C	4 °C
-18 [®] Freezer section	-18 °C	-18 °C

Setting the temperature in the fridge section



- Fig. 20 Example illustration
- Carry out action steps according to the illustration.
 Temperature is set.

Setting the temperature in the freezer section



- Fig. 21 Example illustration
- Carry out action steps according to the illustration.
- \triangleright Temperature is set.
- °C/_

🗄 Temperature unit

Use this function to set the temperature unit. You can set degrees Celsius or degrees Fahrenheit as the temperature unit.

Setting the temperature unit



Fig. 22



Fig. 23 Example illustration: Switch from degrees Celsius to degrees Fahrenheit.

- Carry out action steps according to the illustration.
- \triangleright The temperature unit is set.

D1 **D-Value***

Use this function to set the D-Value.

The D-Value specifies whether you are operating your fridge section with a dry rear wall or without a dry rear wall. The rear wall is installed in the appliance as delivered. The D-Value is pre-set to D1.

can remove the rear wall cleaning. You for (see 9.4.4 Cleaning the dry rear panel*) In order to operate the appliance without a rear wall, you must set the D-Value to D2.

Note

The declared energy consumption was determined without a dry rear wall. The appliance is fully functional with a dry rear wall but its energy consumption will be slightly higher. Liebherr recommends:

• Operate the appliance with a dry rear wall in order to prevent visible condensate and the food freezing.

Setting the D-Value



Fig. 24



Fig. 25 Example illustration: Switch from D1 to D2. Carry out action steps according to the illustration.

 \triangleright The D-Value is set.



SuperCool

You can use this function to activate or deactivate Super-Cool. If SuperCool is activated, then the appliance increases the cooling capacity. It allows you to achieve lower cooling temperatures. You can activate SuperCool when you would like to cool a large quantity of food quickly.

If the function is active, the appliance operates at higher power. As a result, the appliance's operating noise may be temporarily louder and energy consumption will increase.

Activating SuperCool

Time for activation of the function:

- When you would like to store fresh food in the fridge section: Activate the function when inserting food.



Fig. 26



Fig. 27

- Carry out action steps according to the illustration.
- \triangleright SuperCool is activated.

Deactivating SuperCool

SuperCool is deactivated automatically after 18 hours. However, you can also deactivate SuperCool manually at any time:



Fig. 28



Fig. 29

- Carry out action steps according to the illustration. \triangleright
 - SuperCool is deactivated.
- \triangleright The appliance continues to run in normal mode.
- \triangleright The appliance cools to the temperature set previously.



PowerCool

You can use this function to activate or deactivate Power-Cool. PowerCool ensures optimised temperature layers for cooling your food.

The function applies to the fridge section.

Application:

- At higher room temperatures (as of approx. 35 °C)

- At high humidity, e.g. on summer days
- When storing moist food, in order to prevent condensate forming in the interior

Note

The fan may also run even if the function is deactivated. It therefore ensures even temperature distribution in the appliance.

If the function is active, the device operates at higher power. As a result, the device's operating noise may be temporarily louder and energy consumption will increase.

Activating PowerCool



Fig. 30



Fig. 31

- Carry out action steps according to the illustration.
- \triangleright PowerCool is activated.

Deactivating PowerCool



Fig. 32



Fig. 33

- Carry out action steps according to the illustration.
- \triangleright PowerCool is deactivated.

You can use this function to activate or deactivate SuperFrost. If SuperFrost is activated, then the appliance increases the freezing capacity. It allows you to achieve lower freezing temperatures.

Application:

- Quickly freeze fresh food through to the core.
- This ensures that the nutrition, appearance and taste of frozen food is maintained.
- Increase the cold reserve in stored frozen food before defrosting the appliance.

If the function is active, the appliance operates at higher power. As a result, the appliance's operating noise may be temporarily louder and energy consumption will increase.

Activating SuperFrost

Make sure that the following requirements are fulfilled:

Freezing quantity and time for activation of SuperFrost are taken into account. (see Freezing food using SuperFrost)



Fig. 34



Fig. 35

- Carry out action steps according to the illustration.
- ▷ SuperFrost is activated.

Deactivating SuperFrost

SuperFrost is automatically deactivated after 56 to 72 hours depending on the quantity of the food inserted. However, you can also deactivate SuperFrost manually at any time:



Fig. 36



Fig. 37

- Carry out action steps according to the illustration.
- SuperFrost is deactivated.
- \triangleright The appliance continues to run in normal mode.
- \triangleright The appliance cools to the temperature set previously.

Start defrosting cycle

Use this function to start the automatic defrosting cycle manually if it does not start automatically in the event of a fault.

Starting defrosting cycle







Controls

- Carry out action steps according to the illustration.
- Defrosting cycle has started: Icon flashes until defrosting cycle is automatically completed.
- \triangleright When defrosting cycle is finished: The device continues to run in normal mode.

Cancelling defrosting cycle

The defrosting cycle will be stopped automatically. However, you can also cancel the defrosting cycle at any time during the defrosting process:



Fig. 40

- Carry out action steps according to the illustration.
- \triangleright Defrosting cycle is cancelled.
- ▷ The device continues to run in normal mode.

PartyMode

You can use this function to activate or deactivate Party-Mode. PartyMode activates various functions that are useful for a party.

PartyMode activates the following functions:

- SuperCool
- SuperFrost

You can adjust all listed functions individually and flexibly. When you deactivate PartyMode, all changes are discarded.

If the function is active, the device operates at higher power. As a result, the device's operating noise may be temporarily louder and energy consumption will increase.

Activating PartyMode



Fig. 41



Fig. 42

- Carry out action steps according to the illustration.
- \triangleright PartyMode and the associated functions are activated.
- The current temperature flashes until the target temperature is reached.

Deactivating PartyMode

The PartyMode is automatically deactivated after 24 seconds. However, you can also deactivate PartyMode manually at any time:



Fig. 43



Fig. 44

- Carry out action steps according to the illustration.
- \triangleright PartyMode is deactivated.
- The appliance cools to the temperature set previously: The current temperature flashes until the target temperature is reached.



You can use this function to activate or deactivate Holiday-Mode. If you activate HolidayMode, the fridge section is set to 15 °C. This saves you energy during longer periods of absence and prevents bad odours and growth of mould.

Appliance status when HolidayMode is active

Fridge section cools to 15 °C.

EasyFresh cools to 15 °C.

The set temperature is maintained in the freezer section.

PartyMode is deactivated.

SuperCool is deactivated.

PowerCool is deactivated.

Activating HolidayMode

- Empty the fridge section completely.
- Empty EasyFresh completely.



Fig. 45



Fig. 46

- Carry out action steps according to the illustration.
- \triangleright HolidayMode is activated.
- ▷ Temperature display shows HolidayMode symbol.

Deactivating HolidayMode





Fig. 48

- Carry out action steps according to the illustration.
- ▷ HolidayMode is deactivated.
- \triangleright The appliance cools to the temperature set previously.

You can use this function to activate or deactivate SabbathMode. If you activate this function, some electronic functions are switched off. As a result, your device meets the religious requirements for Jewish holidays such as Sabbath and complies with STAR-K Kosher certification.

Device status when SabbathMode is active

The status display shows SabbathMode permanently.

All functions on the display are locked except for the **Deactivate SabbathMode function**.

Active functions remain active.

The display remains bright when you close the door.

The interior lighting is deactivated.

Reminders are not implemented. The set time interval stops.

Reminders and warnings are not displayed.

There is no door alarm.

There is no temperature alarm.

The defrosting cycle operates only for the specified time, without considering the appliance consumption.

After a power failure, the appliance returns to SabbathMode.

Device status

Note

This appliance has certification from the "Institute for Science and Halacha". (www.machonhalacha.co.il)

You can find a list of STAR-K-certified appliances at www.star-k.org/appliances.

Activating SabbathMode

Danger of food poisoning from spoiled food!

If you have SabbathMode activated and a power failure occurs, no message appears in the status display about the power failure. Once the power is restored, the appliance continues to operate in SabbathMode. The power failure may mean that food spoils and the consumption of this food could lead to food poisoning.

After a power failure:

Do not consume food that was frozen and has thawed out.



Fig. 49



Fig. 50

- Carry out action steps according to the illustration.
- \triangleright SabbathMode is activated.
- \triangleright The status display shows SabbathMode permanently.

Deactivating SabbathMode

The SabbathMode is automatically deactivated after 80 hours. However, you can also deactivate SabbathMode manually at any time:



Fig. 51

Carry out action steps according to the illustration.
 SabbathMode is deactivated.



You can use this function to activate or deactivate Energy saving mode. If energy saving mode is activated, the energy consumption decreases and the temperature in the device increases. The food remains fresh, but the shelf life is shortened.

Temperature zone	Recommended setting (see Setting the temperature in the fridge section)	Temperature with active E- Saver	
5 ° Fridge section	4 °C	7 °C	
-18° Freezer section	-18 °C	-16 °C	

Temperatures





Fig. 52



Fig. 53

- Carry out action steps according to the illustration.
- ▷ Energy saving mode is activated.

Deactivating E-Saver

Controls



Fig. 55

- Carry out action steps according to the illustration.
- \triangleright Energy saving mode is deactivated.



You can use this function to activate or deactivate Cleaning-Mode. CleaningMode enables the appliance to be cleaned conveniently.

This setting applies to the fridge section.

Application:

- Clean the fridge section. (see 9.4 Cleaning the appliance)

Device status when CleaningMode is active

The status display shows CleaningMode permanently.

The fridge section is switched off.

Interior lighting is activated.

The reminders and warnings are not displayed. No signal tone sounds.

Device status

Activating CleaningMode



Fig. 56



Fig. 57

- Carry out action steps according to the illustration.
- ▷ CleaningMode is activated.
- Dash The status display shows CleaningMode permanently.

Deactivating CleaningMode

CleaningMode is deactivated automatically after 60 minutes. However, you can also deactivate Cleaning-Mode manually at any time:



Fig. 58

- Carry out action steps according to the illustration.
- \triangleright CleaningMode is deactivated.
- Dash The appliance cools to the temperature set previously.

Display brightness

Use this function to set the display brightness in stages.

You can select the following brightness levels:

- 40 %
- 60 %
- 80 %
- 100 % (pre-setting)

Setting the brightness



Fig. 59



Fig. 60 Example illustration: Switch from 80 % to 60 %. Carry out action steps according to the illustration.

 \triangleright The brightness is set.



Door alarm

Use this function to activate or deactivate the door alarm. The door alarm sounds if the door is open for too long. The door alarm is activated on delivery. You can set how long the door may be open before the door alarm sounds.

The following values can be set:

- 1 minute
- 2 minutes
- 3 minutes
- Off

Setting the door alarm



Fig. 61



Fig. 62 Example illustration: Change door alarm from 1 minute to 3 minutes.

- Carry out action steps according to the illustration.
- \triangleright The door alarm is set.

Deactivating the door alarm



Fig. 64



Fig. 65

Carry out action steps according to the illustration. ► \triangleright The door alarm is deactivated.

Input lock

You can use this function to activate or deactivate the input lock. The input lock prevents the appliance being operated accidentally, e.g. by children.

Application:

- Avoid unintentional modification of functions.
- Avoid unintentional switching off of the device.
- Avoid unintentional temperature setting. _

Activating the input lock

If you activate the input lock, you can continue to navigate in the menus but you cannot select or change other functions.



Fig. 66



Fig. 67

- Carry out action steps according to the illustration.
- \triangleright Input lock is activated.

Deactivating the input lock



Fig. 68



Fig. 69

Carry out action steps according to the illustration. \triangleright Input lock is deactivated.



Device information

Use this function to indicate the model name, index, serial number and service number of your device. You will need the device information when you contact customer service. (see 10.4 Customer Service)

This function also opens the Advanced menu. (see 3 Functionality of the Touch display)

Indicating the device information



Fig. 70



Fig. 71

- Carry out action steps according to the illustration.
- \triangleright Display indicates device information.

Software

Use this function to indicate the software version of your device.

Indicating the software version



Fig. 72

UI SW: XXXXXXX PB SW: XXXXXXXX	
Software	

Fig. 73

Carry out action steps according to the illustration. ▷ Display indicates software version.



Reminder

Use this function to activate or deactivate the reminders. The function is activated on delivery.

If the function is activated, the following reminders will appear:

Replace the FreshAir activated carbon filter (see Replace the FreshAir activated carbon filter)

Activating the reminder



Controls



Fig. 75

- Carry out action steps according to the illustration.
- \triangleright Reminder is activated.

Deactivating the reminder



Fig. 76



Fig. 77

- Carry out action steps according to the illustration.
- ▷ Reminder is deactivated.

Demo mode

Demo mode is a special feature for dealers who want to demonstrate appliance features. If you activate demo mode, all refrigeration functions are deactivated.

If you switch on your appliance and "Demo" appears in the status display, then demo mode is already activated.

If you activate and then deactivate demo mode, the appliance will be reset to factory defaults. (see Resetting to factory settings)

Activating demo mode



Fig. 78



Fig. 79

- Carry out action steps according to the illustration.
- ▷ Demo mode is activated.
- \triangleright Appliance is switched off.
- Switch on the appliance. (see 4.1 Switching on appliance (first use))
- Dash "DEMO" appears in the status display.

Deactivating demo mode





Controls

Fig. 81

- Carry out action steps according to the illustration.
- ▷ Demo mode is deactivated.
- ▷ Appliance is switched off.
- Switch on the appliance. (see 4.1 Switching on appliance (first use))
- \triangleright Appliance is reset to factory settings.

ſ

Resetting to factory settings

Use this function to reset all settings to factory defaults. All settings you have made so far are reset to their original settings.

Performing a reset



Fig. 82



Fig. 83

- Carry out action steps according to the illustration.
- ▷ Device is reset.
- \triangleright Device is switched off.
- Restart the device. (see 4.1 Switching on appliance (first use))

7.3 Messages

There are two categories of messages:

Category	Importance
Warning	Warnings appear in the event of a door alarm or malfunction.
	Simple warnings can be cancelled by yourself. In the event of serious malfunctions, you must contact customer service. (see 10.4 Customer Service)
Reminder	Reminders remind you of general processes. You can carry out these operations to end the message.

7.3.1 Overview of warnings

Behaviour of the appliance in the event of warnings:

- Warning appears on the display.
- The alarm tone sounds at an ever-increasing volume.
- The interior lighting pulsates for some warnings.

Message	Cause	Exit the message
Door alarm	The message appears if the door is open for too long.	

Message	Cause	Exit the message
×	The message appears if the freezing temper- ature has risen due to a power failure.	
Power outage alarm		
	The message appears if the freezing temper- ature does not corre- spond to the set temperature.	steps (see Tempera-
Temperature alarm		
Error	The message appears if there is an appliance error. A component of the appliance has a fault.	steps

7.3.2 Ending warnings

Door alarm



- Fig. 84 Example illustration
- Carry out action steps according to the illustration.
- or-▶ Close the door.

 \triangleright The display returns to the status indicator.

You can set how long the door may be open before the door alarm sounds. (see Setting the door alarm)

Power outage alarm

When the power failure has ended, the appliance cools down to the previously set target temperature.



Fig. 85 Example illustration

- Press the confirmation symbol.
- \triangleright Warmest freezing temperature is displayed.
- \triangleright If the freezing temperature was below -9 °C: Food can still be consumed.
- If the freezing temperature has risen above -9 °C: Check the food.
- Press the confirmation symbol.
- > The display returns to the status indicator: Current temperature and target temperature are displayed.

Features

Temperature alarm

Temperature differences can be caused by:

- You have put in warm, fresh food.
- Too much warm air has got in while you were sorting out the freezer or removing items.
- There has been a longer power failure.
- The appliance is faulty.
- Eliminate causes.
- Dash The appliance cools to the target temperature set previously.



Fig. 86 Example illustration

- Press the confirmation symbol.
- \triangleright Warmest freezing temperature is displayed.
- \triangleright If the freezing temperature was below -9 °C: Food can still be consumed.

If the freezing temperature has risen above -9 °C: Check the food.

- Press the confirmation symbol.
- The display returns to the status indicator: Current temperature and target temperature are displayed.

Error



Fig. 87 Example illustration

- Press the confirmation symbol.
- \triangleright Error code is displayed.
- Note the error code.
- Press the confirmation symbol.
- \triangleright The display returns to the status indicator.
- Contact Customer Service. (see 10.4 Customer Service)

7.3.3 Overview of reminders

Behaviour of the appliance during reminders:

- Reminder appears on the display.
- Alarm tone sounds.
- The interior lighting pulsates for some reminders.

Message	Cause	Exit the message
FreshAir Replace the Fres- hAir activated carbon filter	appears when the activated carbon	Carry out action steps (see Replace the FreshAir acti- vated carbon filter) .

7.3.4 Ending reminders

Replace the FreshAir activated carbon filter

Liebherr recommends: Replace the FreshAir activated carbon filter every 6 months.

Note

FreshAir activated charcoal filters can be purchased from the Liebherr-Hausgeräte store at home.liebherr.com/shop/de/deu/zubehor.html.



Fig. 88 Example illustration

- Press the confirmation symbol.
- Replace the activated carbon filter. (see 9.1 FreshAir carbon filter)
- \triangleright Activated carbon filter ensures optimum air quality in the cooling unit.
- \triangleright Reminder appears again after 6 months.

If you no longer wish to receive this reminder, you can deactivate it. (see Deactivating the reminder)

8 Features

8.1 Door rack

8.1.1 Move/remove the door rack



- Fig. 89
- Slide the rack upwards.
- Pull forwards.
- Re-insert it in reverse order.

8.1.2 Disassembling the door rack

The door rack can be taken apart for cleaning.



Fig. 90



Fig. 91

Disassemble the door rack.

8.2 Shelves

8.2.1 Adjusting/removing the shelves

The shelves are prevented from being pulled out accidentally by pull out stops.



Fig. 92

- Lift the shelf and pull forward.
- \triangleright Line up the side runner.
- Adjust the height of the shelf: Lift or lower it to the desired height and slide it in.

-or-



Fig. 93

- ▶ Remove the shelf completely: Pull it out to the front.
- Easier removal: Set the shelf at an angle.
- ► Insert the shelf again: Slide it in all the way.
- \triangleright The pull-out stoppers point downwards.
- \triangleright The pull-out stoppers are behind the front support.

You can also remove the shelf above the EasyFresh compartments.



Fig. 94

Removing the shelf:

▶ Lift the shelf at the front and back.

Pull it out towards you.

Do not store any goods on the compartment cover below! Inserting the shelf:

- Place the shelf at an angle, sloping down towards the back.
- \triangleright The pull-out stoppers point downwards.
- Slide the shelf into place.

8.2.2 Dismantling the shelves

The shelves can be dismantled for cleaning.



Fig. 95

- Dismantling the shelf.
- 8.3 Dividing shelf*

8.3.1 Using the dividing shelf

The shelves are prevented from being pulled out accidentally by pull out stops.



Fig. 96

Push the dividing shelf underneath as shown.



Fig. 97

Adjusting the height:

- Pull the glass panels out Fig. 97 (1) from the front, one at ► a time.
- ► Release the support rails and click in at the height you want.
- Slide in the glass panels one at a time.
- > Flat pull-out stoppers at the front, right behind the support rails.

▷ High pull-out stoppers at the back.

Using both shelves:

- Hold the glass panel with one hand and pull it to the front. \triangleright
 - The glass panel Fig. 97 (1) and trim strip are at the front.
- ▷ The stops *Fig. 97 (3)* point down.

8.4 VarioSafe *

The VarioSafe offers space in the refrigerator compartment for small groceries, packages, tubes and jars, for example.



- Fig. 98
- VarioSafe drawer
 Side panels with ribs

for VarioSafe drawer

- (3) Recesses on the left and right side panel
- (4) Stop edge

8.4.1 Inserting the VarioSafe



Fig. 99

Insert the VarioSafe into the fridge section at an angle Fig. 99 (1) until the recesses in the side Fig. 99 (2) of the VarioSafe are at the level of the support rib in the fridge section.



Fig. 100

Set VarioSafe straight. *Fig. 100 (1)*

▶ Lift VarioSafe at the front. *Fig. 100 (2)*



Fig. 101

- ► Lift VarioSafe up toward the front.
- Push VarioSafe in to the rear.
- Lower VarioSafe.
- \triangleright VarioSafe audibly engages.
- ▷ VarioSafe is inserted.

8.4.2 Repositioning the VarioSafe

You can move the VarioSafe as a whole in the refrigerator compartment.





Lift VarioSafe at the front.



Pull VarioSafe forwards until the recesses in the side of the VarioSafe are at the level of the support rib in the refrigerator compartment. Fig. 103 (1) Move VarioSafe up or down in the refrigerator compartment until the desired height is reached. Fig. 103 (2)



Fig. 104

- ► Lift VarioSafe at the front.
- ▶ Push VarioSafe in to the rear.
- \triangleright VarioSafe audibly engages.
- ▷ VarioSafe is offset in height.

8.4.3 Moving the VarioSafe drawer

You can use the VarioSafe drawer at two different heights. If you would like to store taller foodstuffs in the VarioSafe drawer, slide the VarioSafe drawer in on the bottom rib. If you would like to store smaller foodstuffs in the VarioSafe drawer, slide the VarioSafe drawer in on the top rib.



Fig. 105

- ▶ Pull out the VarioSafe drawer as far as it will go.
- ► Lift the VarioSafe drawer up at the front.
- Remove the VarioSafe drawer to the front.



Fig. 106

- Lift the VarioSafe drawer up at the front.
- ▶ Place the VarioSafe drawer behind the stoppers on desired rib *Fig. 106 (1)* or *Fig. 106 (2)*.
- ▷ VarioSafe drawer is offset in height.

8.4.4 Removing the VarioSafe

You can remove the VarioSafe as a whole.





► Lift VarioSafe at the front.



Fig. 108

▶ Pull VarioSafe forwards *Fig. 108 (1)* until the recesses in the side of the VarioSafe are at the level of the support rib in the fridge section. *Fig. 108 (2)*



- Set VarioSafe in refrigerator compartment at an angle. Fig. 109 (1)
- Take VarioSafe out to the front. *Fig. 109 (2)*
- \triangleright VarioSafe is removed.

8.4.5 Disassembling the VarioSafe

You can disassemble the VarioSafe into its individual parts if you want to clean the VarioSafe or if you need to install or remove parts.



Fig. 110

- Remove VarioSafe as a whole. (see 8.4.4 Removing the VarioSafe)
- Disassemble VarioSafe according to the illustration.

8.5 Drawers

You can remove the drawers for cleaning.

You can remove the drawers to use VarioSpace.

The way to remove/insert the drawers varies depending on the pull-out system. Your appliance can contain various pull-out systems.

Note

The energy consumption increases and the cooling power goes down if ventilation is not sufficient.

- Leave the bottom drawer in the appliance!
- Always leave the fan air vents clear on the back wall!

8.5.1 Drawer on appliance base or glass shelf

The drawer runs directly on the appliance base or on a glass shelf. There are no rails.

When you remove the drawers, you can use the glass shelves below them as storage shelves.

Removing drawer



Fig. 111

• Remove drawer as shown in the illustration.

Inserting drawer



Fig. 112

▶ Insert drawer as shown in the illustration.

8.5.2 Drawer on rails

Removing drawer



Fig. 113

Remove drawer as shown in the illustration.

Inserting drawer



Fig. 114

▶ Insert drawer as shown in the illustration.

8.6 EasyFresh-Safe cover

You can remove the compartment cover for cleaning.

8.6.1 Removing the compartment cover



Fig. 115

When the drawers are removed:

- ▶ Pull the lid up at the front to the opening in the retaining parts *Fig. 115 (1)*.
- ▶ Lift from the back and pull it up and out *Fig. 115 (2)*.

8.6.2 Inserting the compartment cover



Fig. 116

If the text THIS SIDE UP points upwards:

- Insert the lip of the cover over the opening of the rear bracket Fig. 116 (1) and click into place Fig. 116 (2).
- Position the cover where you want it (see 8.7 Adjusting the moisture levels).

8.7 Adjusting the moisture levels

You can adjust the moisture in the drawer yourself by adjusting the compartment cover.

The compartment lid is attached to the drawer and can be hidden by a shelf or additional drawers.



Fig. 117

Low air humidity

- Open the drawer.
- Slide the compartment cover forwards.
- \triangleright With the drawer closed: Gap between the cover and the compartment.
- \triangleright The air moisture in the Safe decreases.

High air moisture

- Open the drawer. ►
- Slide the cover back.
- \triangleright With the drawer closed: The cover seals the compartment.
- The air moisture in the Safe increases. \triangleright
- If there is too much moisture in the compartment: Choose the setting "low air moisture".
- -or-Remove any excess moisture with a cloth.

8.8 Glass shelves

You can remove the glass shelves under the drawers for cleaning.

You can remove the glass shelves under the drawers to use VarioSpace.

8.8.1 Removing / inserting the glass shelf

Make sure that the following requirements are fulfilled:

Glass shelf under the drawer: The drawer has been removed. (see 8.5 Drawers)

Removing glass shelf



Fig. 118 Example illustration of glass shelf

- ▶ Lift glass shelf at the front. *Fig. 118 (1)*
- Take out glass shelf to the front. Fig. 118 (2)

Inserting glass shelf



Fig. 119 Example illustration of glass shelf

- Position glass shelf at an angle behind the stoppers. (see Fig. 119)
- Lower glass shelf.
- Slide in glass shelf to the back.

8.9 EasyTwist-Ice*

With the EasyTwist-Ice you can make enough ice cubes for the whole household. The EasyTwist-Ice is supplied with water via a water tank.



Fig. 120 Example illustration (1) Freezer drawer with

- (4) Rotary knob
- EasyTwist-Ice (5) Ice cube drawer (2) Body with ice cube tray (3) Water tank

Note

Do not change the position of the freezer drawer with the EasyTwist-Ice in the appliance.

8.9.1 Making ice cubes

The amount of ice cubes you can make in a given period of time with the EasyTwist-Ice depends on the freezer temperature of the appliance. The lower the temperature in the appliance, the more ice cubes you can make.

Features

Maximum number of ice cubes in the ice cube tray:	20 ice cubes
Maximum capacity of the ice cube drawer:	40 ice cubes (equivalent to two ice cube batches)
More information about the time needed for ice cube production:	

Make sure that the following requirements are fulfilled: Components of the EasyTwist-Ice have been cleaned.

Filling the water tank

Risk of poisoning due to contaminated water! • Only fill the water tank with potable water.

NOTICE

Sugar-content liquids! Damage to EasyTwist-Ice.

Only fill with cold drinking water.

Note

Using filtered, decarbonised water ensures the best-tasting drinking water for your ice cubes.

This water quality can be achieved using a table water filter of the kind available in trade retail outlets.

Always fill the water tank only with filtered, decarbonised drinking water.



Fig. 121

- Pull out freezer drawer as far as it will go.
- ▶ Lift the water tank at the recess *Fig. 121* (1).
- ▶ Remove the water tank by lifting it upwards. *Fig. 121 (2)*
- ▶ Fill the water tank with drinking water up to the mark *Fig. 121 (3)*.



Fig. 122

- Position the water tank at the front. Fig. 122 (1)
- Lower the water tank at the rear. Fig. 122 (2)
- Slide in the freezer drawer.

Releasing the ice cubes

Make sure that the following requirements are fulfilled:

- □ The required time for the production of ice cubes has been observed. (see 10.1 Technical specifications)
- □ Freezer drawer is fully inserted.
- Ice cube drawer is fully inserted.
- ▶ Turn the rotary knob *Fig. 120 (4)* clockwise as far as it will go.
- ▷ Ice cubes fall from the ice cube tray into the ice cube drawer *Fig. 120 (5)*.
- If all the ice cubes do not come out of the ice cube tray:
- ▶ Turn the rotary knob clockwise several times to the stop.

8.10 VarioSpace



Fig. 123

You can remove drawers and glass panels from your appliance. This provides more room for large food items such as poultry, joints of meat, large game, and tall baked products. You can then freeze these items whole for later preparation.

Note the weight limits on the drawers and glass panels (see 10.1 Technical specifications).

8.11 Bottle holder

8.11.1 Using the bottle holder



Fig. 124

▶ Push the bottle holder onto the bottles.

 \triangleright The bottles are prevented from falling over.

8.11.2 Removing the bottle holder



Fig. 125

• Move the bottle holder all the way to the right.

Push the bottle holder to the back to remove.

9 Maintenance

9.1 FreshAir carbon filter

The FreshAir carbon filter is in the compartment above the fan.

It guarantees the best air quality.

- □ Replace the carbon filter every 6 months.
- When the reminder is set, a message on the display prompts you to change it.
- The carbon filter can be disposed of with the regular household waste.

Note

FreshAir activated charcoal filters can be purchased from the Liebherr-Hausgeräte store at home.liebherr.com/ shop/de/deu/zubehor.html.

9.1.1 Removing the FreshAir carbon filter



Fig. 126

- ▶ Pull out the compartment *Fig. 126 (1)*.
- Remove the carbon filter *Fig. 126 (2)*.

9.1.2 Inserting the FreshAir carbon filter



Fig. 127

Insert the carbon filter as shown in the diagram Fig. 127 (1).

- The carbon filter clicks into place. If the carbon filter is pointing downwards:
- Push the compartment in Fig. 127 (2).
- \triangleright The carbon filter is now ready for use.

9.2 Disassembling / assembling pullout systems

9.2.1 Notes on disassembly

You can disassemble some of the pull-out systems for cleaning. Your appliance can contain a variety of pull-out systems.

The following pull-out systems can be disassembled or cannot be disassembled:

Pull-out system			can be disassembled / cannot be disassembled
Drawer on appliance glass shelf	base	or	cannot be disassembled
Drawer on rails			cannot be disassembled

9.3 Defrosting the appliance

9.3.1 Defrosting the fridge compartment

Defrosting is performed automatically. The water from the thawing process drains through the outlet and evaporates.

Water drops or a thin layer of frost or ice can form on the back wall; this is a completely normal part of the appliance's function. This must not be removed.*

A layer of frost or ice can from briefly due to the energyoptimised control of the device.*

 Clean the drain opening at regular intervals. (see 9.4 Cleaning the appliance)

9.3.2 Defrosting the freezer compartment with NoFrost

Defrosting is performed automatically with the NoFrost system. The moisture is deposited on the evaporator, is periodically defrosted and evaporates.

The appliance does not have to be defrosted.

9.4 Cleaning the appliance

9.4.1 Ready



Danger of electric shock!

 Remove the refrigerator connector or interrupt the power supply.

Risk of fire ▶ Do not damage the refrigeration circuit.

- Empty the appliance.
- Remove mains connector.
- -or-
- Activate CleaningMode. (see CleaningMode)

9.4.2 Clean the housing

NOTICE

Improper cleaning!

- Damage to the appliance.
- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.

Risk of injury and damage as a result of hot steam!

Hot steam can lead to burns and can damage the surfaces.Do not use any steam cleaners!

▶ Wipe the housing down with soft, clean cloth. If very dirty, use lukewarm water with a neutral cleaner. Glass surfaces can also be cleaned with glass cleaner.

9.4.3 Cleaning the interior

NOTICE

Improper cleaning!

Damage to the appliance.

- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.
- Plastic surfaces: clean by hand with a soft clean cloth, lukewarm water and a little detergent.
- Metal surfaces: clean by hand with a soft clean cloth, lukewarm water and a little detergent.
- Drain hole: remove deposits using a thin item (for example a cotton bud).

9.4.4 Cleaning the dry rear panel*

You can remove the dry rear panel for cleaning.

Removing the rear panel

Remove all equipment parts.



Fig. 128

- ► Hold the rear panel with both hands at the bottom and pull downward vigorously at the same time.
- Pull the rear panel out to the front by the bottom end.
 The rear panel has been removed.
- If you want to continue operating the appliance with the rear panel removed:
- Set the D-Value to D2. (see D-Value*)

Inserting the rear panel



Fig. 129

- Make sure the appliance is completely empty.
- Slide in the rear panel from below to the top.
- Press back vigorously on the left-hand side of the rear panel.
- \triangleright The rear panel clicks into place.
- ► Insert the equipment parts.
- Set the D-Value to D1. (see D-Value*)

9.4.5 Clean the components

NOTICE

Improper cleaning!

- Damage to the appliance.
- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.

Clean with a soft, clean cloth, lukewarm water and some detergent:

- Door rack
- Shelf
- Dividing shelf*
- VarioSafe*
- EasyFresh-Safe cover
- Drawer
- Components of the EasyTwist-Ice*

Wash in the dishwasher up to 60 °C:

- Door rack
- Bottle rack
- Holder of the dividing shelf*
- Ice cube tray*
- ▶ To disassemble components: see the relevant section.
- Clean the components.

9.4.6 Cleaning the EasyTwist-Ice*

Clean the EasyTwist-Ice in the following situations:

- First use
- Not using for more than 48 hours
- When cleaning is required

Dismantling the EasyTwist-Ice

Make sure that the following requirements are fulfilled:

- □ The drawer has been removed. (see 8.5 Drawers)
- □ The drawer is placed on a table.

Maintenance



Fig. 130

- Removing the water tank: Lift the water tank by the ► recess Fig. 130 (1).
- Remove the water tank Fig. 130 (2) upwards.
- Remove the ice cube drawer Fig. 130 (3) to the front.



Fig. 131

- ▶ Removing the EasyTwist-Ice body: Use your finger to push the tab Fig. 131 (4) down and use your other hand to lift the EasyTwist-Ice body Fig. 131 (5) from behind at the same time.
- Remove the EasyTwist-Ice body from the freezer drawer.



Fig. 132

- ▶ Removing the EasyTwist-Ice body cover: Push the tabs Fig. 132 (6) on both sides of the EasyTwist-Ice body with one hand.
- Use the other hand to remove the cover Fig. 132 (7) upwards.
- \triangleright EasyTwist-Ice is dismantled into four parts. (see Fig. 133)



- (1) EasyTwist-Ice body (3) Cover

with ice cube tray (2) Water tank

(4) Ice cube drawer

NOTICE

Risk of damage due to improper dismantling!

Equipment breaking, jumping and cracking. If you dismantle the EasyTwist-Ice body further, you may damage the rotary knob or other parts of the EasyTwist-Ice body.

- ▶ Only dismantle the EasyTwist-Ice into the components shown. (see Fig. 133)
- Clean the EasyTwist-Ice body Fig. 133 (1) as a whole.

Cleaning the EasyTwist-Ice

Make sure that the following requirements are fulfilled:

- □ The EasyTwist-Ice is dismantled. (see Dismantling the EasyTwist-Ice)
- ► Clean the ice cube drawer, water tank, cover and Easy-Twist-Ice body with warm water and a little detergent.
- Dry all cleaned components thoroughly with a dry cloth.
- \triangleright The EasyTwist-Ice is clean.

Installing the EasyTwist-Ice



- ▶ Installing the EasyTwist-Ice body cover: Place the cover on the front. Fig. 134 (1)
- ► Lower the cover at the rear. Fig. 134 (2)
- \triangleright The cover locks into both tabs *Fig. 134 (3)* audibly.

Customer help



Fig. 135

- Installing the EasyTwist-Ice body: Push the axes for the EasyTwist-Ice body into the guides Fig. 135 (4).
- Press the EasyTwist-Ice body Fig. 135 (5) down at the back.
- ▷ The EasyTwist-Ice body locks in audibly.



Fig. 136

▶ Insert the ice cube drawer Fig. 136 (6).

WARNING

Risk of poisoning due to contaminated water!

- Only fill the water tank with potable water.
- Fill the water tank with water.
- Insert the water tank.
- Insert the drawer. (see 8.5 Drawers) If you are using unfiltered water:
- Dispose of ice cubes that were produced 24 hours after initial ice cube production.
- -or-

If you are using filtered water:

Dispose of ice cubes that were produced 48 hours after initial ice cube production.

9.4.7 After cleaning

- ▶ Wipe the appliance and the components dry.
- Connect and switch on the appliance.
- Activate SuperFrost (see 7.2 Appliance functions). The temperature is cold enough:
- Place the food inside. Repeat cleaning regularly.

10 Customer help

10.1 Technical specifications

Temperature range			
Cooling	2 °C to 9 °C		
Freeze	-26 °C to -19	5 °C	
Maximum freezing qu	uantity/24 h		
Freezer compart- ment	See "Freezing capacity/24 h" on the type plate		
Maximum component capacity			
Features	Appliance width 550 mm (see instal- lation instruc- tions, appliance dimen- sions)		Appliance width 700 mm (see instal- lation instruc- tions, appli- ance dimen- sions)
Drawer on glass shelf (see 8.5.1 Drawer on appliance base or glass shelf)	12 kg	15 kg	

Ice cube production with EasyTwist-Ice*

Time required at -18 °C

Time required with SuperFrost activated approx. 3 h

Lighting	
Class ¹	Light source
This product contains one or more energy efficiency class G light sources.	LED

approx. 5.5 h

¹ The appliance may contain light sources with different energy efficiency classes. The lowest energy efficiency class is indicated.

10.2 Operating noises

The appliance makes different noises when it is on.

- At higher temperatures the appliance uses less energy but works for longer. It is quieter.
- At lower temperatures the food is cooled faster. It is louder.

Examples:

- Functions on (see 7.2 Appliance functions) .
- Fan running .
- Food recently added
- High ambient temperature
- Door open for a while

Noise	Possible cause	Type of noise
Bubbling and splashing	Coolant flowing into the cooling circuit.	Normal operating noise

Customer help

Noise	e Possible ca		cause	Type of noise	
Hissing		Coolant into the circuit.		Nori nois	mal operating e
Humming		is cooli	appliance ng. The depends cooling	Nori nois	mal operating e
Humming rustling	and	The fan is running.		Nori nois	mal operating e
Clicking	Compone switched off.		nts are on and	Nori nois	mal switching e
Rattling humming	or	Valves or working.	flaps are	Nori nois	mal switching e
Noise	Possible cause		Type of no	noise Lifting	
Vibration	Improper setup		Defective noise		Level the appliance using the adjustable feet.

Noise	Possible cause	Type of noise	Lifting
Rattling	Components, items inside the appliance	Defective noise	Secure components. Leave enough space between the items.

10.3 Technical fault

Your appliance is designed and built to ensure it works reliably and has a long service life. In the unlikely event that a fault occurs during operation, please check whether it is due to an operating error. If so, you will be charged for the callout and repair costs even if it falls within the warranty period.

You can fix the following faults yourself.

10.3.1 Appliance function

Defect	Cause	Remedy
The appliance is	→ The appliance is not switched on.	 Switch the appliance on.
not working.	→ The power plug is not properly plugged into the socket.	 Check the power plug.
	→ There is something wrong with the power outlet fuse.	 Check the fuse.
	→ Power cut	 Keep the appliance closed. Protecting food: Lay freezer packs on top of the food or use another freezer if the power is off for a prolonged period. Do not re-freeze defrosted food,
	→ The appliance plug does not fit the appliance properly.	 Check the appliance plug.
Temperature is not cold enough.	→ The appliance door is not closed properly.	 Close the appliance door.
	→ Not enough ventilation.	Keep ventilation grille clear, and clean it.
	→ The ambient temperature is too high.	 Problem solution: (see 1.4 Appliance range of use)
	→ The appliance was opened too many times or for too long.	 Wait to see if the required temperature corrects itself. If not, contact Customer Service. (see 10.4 Customer Service)
	→ Too much fresh food was placed inside without SuperFrost.	 Solution: (see SuperFrost)
	→ The temperature is set incorrectly.	Turn down the temperature and check after 24 hours.
	→ The appliance is too close to a heat source (oven, radiator, etc).	Move the appliance or the heat source.
The door seal is defective or needs to be replaced for another reason.	→ The door seal can be replaced. It can be replaced without the need for special tools.	 Contact Customer Service. (see 10.4 Customer Service)

Shutting down

Defect	Cause	Remedy
The appliance builds up too much ice or condensa- tion.	→ The door seal may have slipped out of its groove.	 Check that the door seal is well fitted in the groove.
The appliance is hot to touch on the outside*.	→ The heat of the refrigeration circuit is used to avoid condensation.	This is normal.

10.3.2 Features

Defect	Cause	Remedy
The internal light	\rightarrow The appliance is not switched on.	 Switch the appliance on.
does not come on.	→ The door was open for longer than 15 minutes.	Interior lighting turns off automatically after approx. 15 min. with the door open.
	→ The LED interior light is faulty or the lid is damaged.	 Contact Customer Service. (see 10.4 Customer Service)

10.4 Customer Service

First check whether you can rectify the fault yourself (see 10 Customer help) . If you cannot rectify the problem, contact Customer Service.

You can find the address in the enclosed brochure "Liebherr-Service" or at home.liebherr.com/service.



Unprofessional repair! Injuries.

- Have any repairs and action not expressly specified on the appliance and mains cable carried out by service personnel only. (see 9 Maintenance)
- A damaged mains cable may only be replaced by the manufacturer, the manufacturer's Customer Service or a similarly qualified person.
- ▶ In the case of appliances with an IEC connector, the change may be made by the customer.

10.4.1 Contacting Customer Service

Make sure that the following appliance information is available:

- □ Appliance name (model and index)
- Service no. (Service)
- Serial no. (S no.)
- Call up the appliance information via the display. (see Device information)

-or-

- Refer to the type plate for appliance information. (see 10.5 Model plate)
- ▶ Note down the appliance information.
- ► Notify customer service: Report errors and the appliance information.
- This will help us to provide you with a faster, more accurate service.
- ► Follow further instructions from Customer Service.

10.5 Model plate

The model plate is behind the drawers on the inside of the appliance.



Fig. 137

- (1) Appliance description (3) Serial no.
- (2) Service no.
- Note the data on the model plate.

11 Shutting down

- Empty the appliance.
- Switch off appliance. (see Switching the appliance off and on)
- Pull the mains plug out of the socket.
- Remove the IEC socket if required: Pull the IEC socket out of the appliance plug and move it to the left and right at the same time.
- Clean appliance. (see 9.4 Cleaning the appliance)
- Leave the door open, so that no unpleasant odours arise.

12 Disposal

12.1 Preparing appliance for disposal



Liebherr uses batteries in some of its appliances. In the EU, for environmental reasons, legislation obliges the end user to remove these batteries before disposing of old appliances. If your appliance contains batteries, a corresponding notice is attached.

- Lamps If you can remove the lamps yourself without destroying them, also remove these before disposal.
- Take the appliance out of operation.
- ▶ If possible: remove lamps without destroying them.

12.2 Disposing of the appliance in an environmentally friendly manner



The appliance still contains valuable materials and must be disposed of separately from unsorted municipal waste.

Lamps

Dispose of removed lamps via the respective collection systems.

For Germany: You can dispose of the appliance free of charge via the class 1 collection containers at the local recycling and recyclable material collection centres. When purchasing a new fridge/freezer, if the sales area > 400 m², retailers will also take back the old appliance free of charge.

Leaking coolant and oil!

Fire. The coolant contained in the appliance is eco-friendly, but also flammable. The oil contained in the appliance is flammable. Escaping coolant and oil can ignite if the concentration is high enough and in contact with an external heat source.

- ► Do not damage the pipelines of the coolant circuit and the compressor.
- Observe the notes on transporting the appliance.
- Transport the appliance without damaging it.
- Dispose of batteries, lamps and the appliance according to the above specifications.



home.liebherr.com/fridge-manuals

EN fridge/freezer

Issue date: 20240710

Part number index: 7083580-01

Liebherr-Hausgeräte Marica EOOD Bezirk Plovdiv 4202 Radinovo Bulgarien